



THE EQUIPMENT FOR THE FULL BODY DECORATION OF COMPLEX SHAPES' PRODUCTS

FEATURES

A monobloc structure for optimized floor space

An ultra-compact, all-stainless steel machine with a 360° housing

An all stainless steel monobloc structure offering an optimized footprint: it includes the applicator head, a shrink tunnel equipped with a height-adjustable system and the electrical cabinets. This machine meets the expectations of brands and subcontractors for the processing of full or empty packagings, from 50 ml to 2L, in plastic, glass or metal containers (aerosol, can, jar or bottle) to apply a shrink sleeve decoration label.



Intuitive graphical touch interface for the operator

A large touch screen that makes it easy to understand and control the machine

The operator controls all the supervision functions throughout production with a large screen featuring a user-friendly graphic interface.

A remote, adjustable and multifunctional feeding unit

Easy access, orientation and multiple functions to fit your line

Operators have easy access to the loading station which is positioned at man height. The magazine can be rotated 360° for better ergonomics and can be upgraded to accommodate different options according to your needs: splicing table, multi-reel holder, marking or micro-perforation...



Steam shrink tunnel with controlled energy consumption

Optimize your carbon footprint, control your energy consumption

The unique and innovative design of the steam shrink tunnel guarantees energy consumption through the combination of three key elements: a lifting and lowering system, a steam diffusion system and an expansion chamber, all of which are sized for each format. This allows for a controlled and repeatable quality of finish.

OPTIONS

Simplicity of implementation for new formats



Splicing table



Multiple checks for a product of high quality



SPECIFICATIONS

Non-contractual information

Machine

Conveyor height	980 +/- 50 mm
Speed	100 bpm
Cutting diameter	100 mm - 130 mm
Steam consumption	From 50 to 150 kg/h
Steam pressure	6 - 8 bars
Electrical consumption	9 kW/h



Packagings

Materials	Glass, plastics, metal...
Shapes	Cylindrical, oval, square, complex shapes
Sizes	From 100 ml to 2L
Products diameter	From 35 to 128 mm
Products height	From 35 to 300 mm

Sleeves

Applications	Full covering
Type of films	PET, RPET ...
Films thickness	From 40 to 90 microns
Finishing	Neutral, printed effects, opaque...



MARKETS & PACKAGING



Contact us



Europe and Eastern Europe
North & South America
Asia, China & Oceania
Africa & Middle East



Corporate Office Sleever Machines Group
ZI Le Val - 15 Avenue Arago
91420 MORANGIS - FRANCE
+ 33 (0)1 69 75 75 76 – www.sleever.com